

Sterile Nitrile Textured Gloves

STN200 Series

Specifications

Physical Properties

| | |
|--------------------------|--------------------------|
| Style | Ambidextrous |
| Length | 12" (300mm) |
| Thickness | 5 mil (0.005") |
| Grip Surface | Microtextured Fingertips |
| Sizes | XS - XXL |
| Cuff | Beaded |
| Colors | White |
| Tensile Strength | >12.5 MPa |
| Elongation at break (%): | >500 |

Technical Properties

| | |
|--|--|
| Particle Levels Class M3.5 (100) | <3000 total particle/cm ² > 0.5um IEST-RP-CC005.2 Method |
| Flouride | < 0.05 ug/cm ² |
| Chloride | < 3.0 ug/cm ² |
| Nitrite | < 0.05 ug/cm ² |
| Nitrate | < 3.00 ug/cm ² |
| Phosphate | < 0.05 ug/cm ² |
| Sulphate | < 3.00 ug/cm ² |
| Total NVR (DI Water) ESD Properties | < 8.00 ug/cm ² At 50-60% Humidity |
| Surface Resistivity | < 10-10 ohm/square per ESD-S11.11 |
| Static Decay | < .5 seconds per RETS-5-003 |
| Cert of Conformance | Available on request |
| Cert of Sterility | Available on request |



All TechNiGlove products are manufactured in ISO9001:2000 and ISO 14001:2004 certified facilities

